



## 2nm 180° Green, double, silver anodized

200-018G2ST

2nm 180° Green, double, silver anodized  
Vertical mounted with 0.75m cables

Specifications	
Number	200-018G2ST
Light Color	Green
Dimensions metric	See drawing
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>5.4cd
Dimensions imperial	See drawing
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	2nm
Included In Package	1 Navigation light, precabled with 0.75 meter shielded marine grade cable, Installation guide
Materials	Silver anodized aluminum 25μ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
EAN	5704438021396
IP rating	IP68
UPC Code	879343021528
Connection	0.7m cable
Current consumption (mA @ 12VDC)	145
Current consumption (mA @ 24VDC)	60
Vessel size	Under 12M,12-20M,20-50M
Weight (Kg)	0.44 Kg

**Specifications**

<b>Weight (Oz)</b>	15.62 Oz
--------------------	----------