



## 6nm 225° Masthead, double + 3nm double 360° white, silver anodized, horizontal mount

300-138+112G2ST-CD

6nm dbl Masthead+3nm dbl 360°white,silver anodized  
Horizontal mounted  
on a cable down aluminium base (P/N 400-035)

Specifications	
Number	300-138+112G2ST-CD
Light Color	White
Dimensions metric	Ø92,5mm x 169mm
Certification	This Navigation Light is certified by DNV, the Declaration of conformity and the certificates can be found on <a href="http://www.lopolight.com">www.lopolight.com</a> under <a href="#">Service &amp; Support</a>
Intensity	>94cd
Dimensions imperial	Ø3.6" x 6.6"
Approved to	COLREG72,EN14744,IEC 60945,IACS E10,USCG,ABS,M.E.D.,DNV,LR
Visibility	3nm
Operating temperature	-25°C to 55°C
Mounting	Horizontal
Materials	Silver anodized aluminum 25µ, PMMA lens, A4 stainless steel screws, Epoxy, Polyurethane
Operating Voltage	20-32VDC
EAN	5704438012349
IP rating	IP68
Power draw (W)	13
UPC Code	879343012342
Connection	Plug connector
Current consumption (mA @ 12VDC)	0

Specifications	
<b>Stock status</b>	Made to order
<b>Current consumption (mA @ 24VDC)</b>	580
<b>Vessel size</b>	Over 50M
<b>Min. feed wire gauge</b>	0.5mm <sup>2</sup> AWG22
<b>Weight (Kg)</b>	2 Kg
<b>Weight (Oz)</b>	70.54 Oz